

DESCRIPTION



RJ45 CONNECTOR UTP CAT. 6 - MOUNTING RACK (250MHZ)

- Unshielded.
- Universal Keystone clamping system.




RJ45 CONNECTOR STP

- Shielded.
- Universal Keystone clamping system.

CHARACTERISTICS

- Connection with and without tools (connectors with self-peeling contacts).
- Compatible with cables: 23 - 26 AWG
- Compatible with both 110 and Krone push down tool.
- Compatible with colors code EIA/TIA568A and EIA/TIA568B.
- Insertion force: 20N max. IEC 60603-7-4 (UTP).
- Insertion force: 30N max. IEC 60603-7-5 (STP).
- Operating temperature: -10°C to 60°C.
- Retention strength: 7,7 kgf.
- Durability: 750 cycles.

CONNECTIONS

TERMINAIS	EIA/TIA 568A		EIA/TIA 568B	
	PAIR	WIRE COLOR	PAIR	WIRE COLOR
 PIN 5	1	WHITE/BLUE	1	WHITE/BLUE
PIN 4		BLUE		BLUE
PIN 1	3	WHITE/GREEN	2	WHITE/ORANGE
PIN 2		GREEN		ORANGE
PIN 3	2	WHITE/ORANGE	3	WHITE/GREEN
PIN 6		ORANGE		GREEN
PIN 7	4	WHITE/BROWN	4	WHITE/BROWN
PIN 8		BROWN		BROWN

DIMENSIONS (mm)

